

SPE Series Single Channel Power Supply Technical Specification

The instrument must be operated continuously for more than 30 minutes at the specified operating temperature to achieve the following specifications

Specifications			
	SPE3103(U)	SPE6103(U)	SPE6063(U)
Input Characteristics			
Supply Voltage	110Vac±15% or 220Vac±15%, please supply power according to the mark on the left of the power input socket on the rear panel of the instrument		
Input Frequency	45~65Hz	45~65Hz	45~65Hz
Input Parameter 1 (110Vac±15%)			
Input Voltage Range	93~127Vac	93~127Vac	93~127Vac
Full Load Input Current	≤5.6A	≤5.6A	≤5.6A
No-Load Input Current	≤300mA	≤300mA	≤300mA
Input Fuse	250V,F10A	250V,F10A	250V,F10A
Input Parameter 2 (220Vac±15%)			
Input Voltage Range	187~253Vac	187~253Vac	187~253Vac
Full Load Input Current	≤2.8A	≤2.8A	≤2.8A
No-Load Input Current	≤150mA	≤150mA	≤150mA
Input Fuse	250V,F5A	250V,F5A	250V,F5A
Rated Output			
Voltage	0~30V	0~60V	0~60V
Current	0~10A	0~10A	0~6A
Power	300W	300W	300W
Efficiency (110Vac, rated load)	80%	80%	80%
Efficiency (220Vac, rated)	85%	85%	85%

load)			
Regulation(CV)			
Load	≤30mV	≤30mV	≤30mV
Line	≤20mV	≤20mV	≤20mV
Regulation(CC)			
Load	≤30mA	≤30mA	≤30mA
Line	≤20mA	≤20mA	≤20mA
Ripple & Noise (Noise bandwidth 20MHz, ripple bandwidth 1MHz, connect 10uF electrolytic capacitor in parallel with 0.1uF ceramic capacitor to the output terminal for testing)			
Voltage (Vp-p)	≤30mV	≤50mV	≤50mV
Voltage (rms)	≤3mV	≤5mV	≤5mV
Current (Ap-p)	≤30mA	≤30mA	≤30mA
Setting Resolution			
Voltage	10mV	10mV	10mV
Current	1mA	1mA	1mA
Readback Resolution			
Voltage	10mV	10mV	10mV
Current	1mA	1mA	1mA
Setting Accuracy			
Voltage	≤0.1%±20mV	≤0.1%±30mV	≤0.1%±30mV
Current	≤0.1%±10mA	≤0.1%±10mA	≤0.1%±10mA
Readback Accuracy			
Voltage	≤0.1%±20mV	≤0.1%±30mV	≤0.1%±30mV
Current	≤0.1%±10mA	≤0.1%±10mA	≤0.1%±10mA
Response time			
Transient recovery time (50%~100% rated load)	≤1ms		
Protective function			
OVP	0~31V	0~61V	0~61V
OCP	0~10.1A	0~10.1A	0~10.1A
OTP	85℃	85℃	85℃
Temperature coefficient of output			
Voltage	100ppm/℃		

Current	200ppm/°C
Temperature coefficient of readback value	
Voltage	100ppm/°C
Current	200ppm/°C
Display	
Display Type	2.8inches color LCD
Resolution	240 × 320 pixels
Color	65536 color,TFT
Environment	
Temperature	Working Temperature:0°C~40°C Storage Temperature:-20°C~60°C
Relative Humidity	≤90%RH; no condensation
Height	2,000 meters
Cooling	Fan cooling, temperature intelligent speed control
Other	
Communication Port	Provides three optional interfaces: USB, LAN, and RS232, compatible with the SCPI communication protocol.
USB Charging Port	5V/1A charging (without U model); Support QC2.0, QC3.0, BC1.2, Apple, Huawei FCP, Samsung AFC quick charge protocol 5V, 9V quick charge output, the maximum power is 12W, beyond the maximum power will turn off the quick charge output (only with U models)
Dimension	82mm(Width)× 142mm(Height)×226mm(Length)
Weight	Approx. 1.5 kg



7007020100133

V1.0.3